

- ✓ Powerful 2300 watt motor
- ✓ - 45°/0°/45° mitre capacity with quick release mitre clamp
- ✓ Spindle lock for easy wheel and accessory changing
- ✓ Deflector protects the user from sparks
- ✓ Oversize guard for added safety
- ✓ On board wrench storage
- ✓ Rubber feet for greater stability
- ✓ Replaceable carbon brushes
- ✓ Supplied with a 4m cable, 355mm cutting disc and a spanner



Bore size (mm)	25,4
Cutting cap. L-shape profile 90° / 45° (mm)	130 x 130 / 100 x 100
Cutting cap. square profile 90° / 45° (mm)	115 x 115 / 95 x 95
Cutting capacity rectangle 90° / 45° (mm)	120 x 115 / 105 x 95
EAN Code	4002395129638
No load speed (rpm)	4280
Power input (W)	2300
Sound power level (Lwa)(dB(A))	102
Sound power level uncertainty (dB(A))	3
Sound pressure level (Lpa)(dB(A))	89
Sound pressure level uncertainty (dB(A))	3
Supplied in	Gift box
Vibration level (m/s <sup>2</sup> )	<2,5
Vibration uncertainty (m/s <sup>2</sup> )	1,5
Weight (kg)	16,5
Wheel size (mm)	355

