

- ✓ Compact and Powerful Sub Compact brushless motor technology delivers up to 280Nm of torque
- ✓ 3 Speed gear box and Autostop provides ultimate control through all applications
- ✓ Sub Compact design provides ultimate user productivity and ergonomics
- ✓ Lightweight tool at only 1.4Kg with PRO18V 2.0Ah pack
- ✓ Only 113mm in length allows tool to fit into tight spaces
- ✓ AUTOSTOP shuts tool off after impact to prevent fastener damage
- ✓ 1/2" Square reception



|                                                                                                              |                      |
|--------------------------------------------------------------------------------------------------------------|----------------------|
| Battery pack capacity (Ah)                                                                                   | -                    |
| Battery supplied                                                                                             | -                    |
| Battery type                                                                                                 | Li-ion               |
| Charger supplied                                                                                             | -                    |
| EAN Code                                                                                                     | 4058546339258        |
| Impact rate (ipm)                                                                                            | 0-3800               |
| LED                                                                                                          | Yes                  |
| Max. torque (Nm)                                                                                             | 280                  |
| No load speed (rpm)                                                                                          | 0-2800               |
| No. of batteries supplied                                                                                    | 0                    |
| Socket retention                                                                                             | Friction Ring        |
| Sound power level uncertainty (dB(A))                                                                        | 107,0 dB (A)         |
| Sound pressure level uncertainty (dB(A))                                                                     | 96,0 dB (A)          |
| Supplied in                                                                                                  | Gift box             |
| Vibration impact tightening of fasteners of the maximum capacity of the tool [m/s <sup>2</sup> ]             | 13 m/s <sup>2</sup>  |
| Vibration impact tightening of fasteners of the maximum capacity of the tool uncertainty [m/s <sup>2</sup> ] | 1,5 m/s <sup>2</sup> |
| Voltage (V)                                                                                                  | 18                   |
| Weight with battery pack (EPTA) (kg)                                                                         | 1,4                  |