

- ✓ Compact and Powerful Sub Compact brushless motor technology delivers up to 280Nm of torque
- ✓ 3 Speed gear box and AUTOSTOP provides ultimate control through all applications
- ✓ Sub Compact design provides ultimate user productivity and ergonomics
- ✓ Lightweight tool at only 1.4Kg with PRO18V 2.0Ah pack
- ✓ Only 114mm in length allows tool to fit into tight spaces
- ✓ AUTOSTOP shuts tool off after impact to prevent fastener damage
- ✓ 1/2" Square reception with friction ring for improved socket retention



Battery pack capacity (Ah)	-
Battery supplied	-
Battery type	Li-ion
Charger supplied	No charger supplied
EAN Code	4058546403454
Impact rate (ipm)	3800
LED	Yes
Max. torque (Nm)	280
No load speed (rpm)	2800
No load speed gear 1 (rpm)	0-850
No load speed gear 2 (rpm)	0-2100
No load speed gear 3 (rpm)	0-2800
No. of batteries supplied	0
Socket retention	Friction Ring
Sound power level (Lwa)(dB(A))	112
Sound power level uncertainty (dB(A))	3
Sound pressure level (Lpa)(dB(A))	101
Sound pressure level uncertainty (dB(A))	3
Vibration impact tightening of fasteners of the maximum capacity of the tool [m/s <sup>2</sup> ]	ah = 11,3m/s <sup>2</sup> / K = 1,5 m/s <sup>2</sup>
Vibration level (m/s <sup>2</sup> )	11.3
Vibration uncertainty (m/s <sup>2</sup> )	1.5
Voltage (V)	18
Weight with battery pack (EPTA) (kg)	1.4 (L1820S)

