

- ✓ High performance motor delivers 3000 strokes per minute and 25.4mm stroke length
- ✓ Lightweight and easy to handle ergonomic design
- ✓ Professional, die-cast aluminium base plate
- ✓ Tool free blade change
- ✓ Variable speed trigger
- ✓ Line of sight blower function to improve user view of workpiece
- ✓ Electronic motor brake
- ✓ Supplied with a plastic shoe cover, 1 multi material blade & dust port attachment



Battery pack capacity (Ah)	-
Battery supplied	-
Battery type	Li-ion
Bevel capacity (°)	45
Charger supplied	No charger supplied
EAN Code	4058546418526
Max. cutting capacity aluminium (mm)	20mm
Max. cutting capacity steel (mm)	10mm
Max. cutting capacity wood (mm)	135mm
No load stroke rate (spm)	3000
No. of batteries supplied	0
Pendulum action	Yes
Pendulum settings	3
Sound power level uncertainty (dB(A))	LW = 94 dB(A) / K = 5 dB(A)
Sound pressure level uncertainty (dB(A))	Lp = 83 dB(A) / K = 5 dB(A)
Stroke length (mm)	25.4
Stroke rate (spm)	3000
Supplied in	Gift box
Vibration cutting boards uncertainty (m/s²)	ah,B = 5,5 m/s² - K = 1,5 m/s
Vibration cutting of sheet metal uncertainty [m/s²]	ah,M = 5,6 m/s² K = 1,5 m/s²
Voltage (V)	18V
Weight with battery pack (EPTA) (kg)	2.36 (L1820S)

