

### PRO 18v BRUSHLESS

- ✓ L-shape brushless SDS Plus Rotary hammer for drilling into concrete up to 26mm
- ✓ 4-mode settings for ultimate application versatility (Rotary Hammer Drilling / Rotary Drilling / Hammer Only / Manual chisel adjustment)
- ✓ Dual rear handle spring loaded vibration dampening system. Significant reduction through tool to reduce user fatigue
- ✓ 2.5 Joule impact energy delivers high performance for drilling, chiseling & light demolition applications
- ✓ PROFLUX™ Brushless Motor for better efficiency
- ✓ Rafter hook for mounting tool when not in use



Battery pack capacity (Ah)	6.0
Battery type	Li-ion
Blow energy (EPTA)(J)	2.5
Charger supplied	80 min
EAN Code	4058546413873
Full load hammer action (bpm)	5000
Max. drilling concrete (mm)	26
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
No load speed (rpm)	0-1500
No. of batteries supplied	2
Sound power level (Lwa)(dB(A))	103
Sound power level uncertainty (dB(A))	3
Sound pressure level (Lpa)(dB(A))	92
Sound pressure level uncertainty (dB(A))	3
Supplied in	Kitbox
Vibration chiseling (m/s <sup>2</sup> )	17.5
Vibration chiselling uncertainty (m/s <sup>2</sup> )	1.5
Vibration drilling (m/s <sup>2</sup> )	18.3
Vibration drilling uncertainty (m/s <sup>2</sup> )	1.5
Voltage (V)	18V
Weight with battery pack (EPTA) (kg)	3.76 (L1860SHD)