

- ✓ High torque brushless motor technology delivers up to 1627Nm of breakaway torque
- ✓ 3 Speed gear box and AUTOSTOP provides ultimate control through all applications
- ✓ AUTOSTOP mode shuts tool off on impact to avoid overtightening
- ✓ 1/2" Friction Ring anvil for optimal socket retention
- ✓ Features HD-SYNC™ Technology which provides up to 20% more power, when combined with our High Demand Pro Lithium-ion PRO18V batteries
- ✓ As part of the PRO18V system of professional powertools, this tool is compatible with any PRO18V battery



| | |
|---|---------------|
| Battery pack capacity (Ah) | - |
| Battery supplied | - |
| Battery type | Li-ion |
| EAN Code | 4058546483005 |
| Impact rate (ipm) | 0-2300 |
| Max. torque (Nm) | 1220 |
| No load speed (rpm) | 1900 |
| No load speed gear 1 (rpm) | 0-600 |
| No load speed gear 2 (rpm) | 0-1300 |
| No load speed gear 3 (rpm) | 0-1900 |
| No. of batteries supplied | 0 |
| Socket retention | Friction Ring |
| Sound power level (Lwa)(dB(A)) | 106 |
| Sound power level uncertainty (dB(A)) | 3 |
| Sound pressure level (Lpa)(dB(A)) | 98 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Speed settings | 3 |
| Supplied in | Gift box |
| Torque settings | 4 |
| Vibration uncertainty (m/s ²) | 1.5 |
| Weight with battery pack (EPTA) (kg) | 3.05 (L1840S) |

