

- ✓ Brushless Plunge / Track saw that delivers high performance and is extremely accurate to complete a high quality finish for plunge cuts and sheet cutting applications
- ✓ 165mm 40 toothed blade for a clean and accurate finish with very little breakout on material
- ✓ Simple and accurate depth of cut adjustment scale for both 'On Track and 'Off Track'
- ✓ Easy to use and adjust beveling function with accurate scale ranging from -1 to 47
- ✓ Maximum depth of cut of 58.5
- ✓ Spring loaded retractable riving knife that keeps material from pinching blade post cut avoiding 'kick back'

Battery pack capacity (Ah)	-
Battery supplied	-
Battery type	Li-ion
Bevel capacity (°)	-1 > 47
Blade diameter (mm)	165
Blade type	40T TCT
Bore size (mm)	20
Charger supplied	-
EAN Code	4058546484002
Max. cutting depth 45° (mm)	42.5
Max. cutting depth with guiderail [mm]	54
Max. cutting depth with guiderail 45° [mm]	38.1
Max. cutting depth 90° (mm)	58.5
No load speed (rpm)	5000
No. of batteries supplied	0
Sound power level (Lwa)(dB(A))	100 dB(A)
Sound power level uncertainty (dB(A))	3 dB(A)
Sound pressure level (Lpa)(dB(A))	92 dB(A)
Sound pressure level uncertainty (dB(A))	3 dB(A)
Supplied in	Gift box
Vibration cutting wood (m/s <sup>2</sup> )	1.7
Vibration cutting wood uncertainty (m/s <sup>2</sup> )	1.5
Voltage (V)	18
Weight with battery pack (EPTA) (kg)	4.7 (L1840SHD)

